

## T50R0UVC2



**Article Number:** 112-05060

**Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg**



Download spec sheet

### Base Data

**Local Order Number** T50R0UVC2

**Type** T50R

**Color** Black (BK)

- Features and Benefits**
- UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.
  - Inside serrations allow for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225.0 N

**Length L (Imperial)** 8.0 "

**Length L (Metric)** 202.0 mm

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 1.97 "

**Bundle Diameter Max. (Metric)** 50.0 mm

**Thickness T (Imperial)** 0.05 "

**Thickness T (Metric)** 1.2 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 5000 Pieces

**Weight (Metric)** 1.3 kg

## Material and Specifications

---

**Material** Polyamide 6.6 UV-stabilized (PA66UV)

**Material Shortcut** PA66UV

**US MILSPEC** MS3367-1-0

**CSA Certified** No

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS compliant (Article 4 - 1)** Yes

**Certification/Specification** MIL 53421  
UL ZODZ.E64139  
MS3367

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No