

2 Megapixel Outdoor IR TVI Bullet Remote Focus Lens





Description: Features: The CBT2S12IFW outdoor bullet camera • 2 Megapixel Resolution provides high quality video at 2 megapixel • 1/3" CMOS Image Sensor resolution over existing coaxial cable. The • 2.8-12mm Remote Focus and Zoom Lens • 10 IR LEDs with an 65 feet (20m) Range infrared LEDs provide illumination for clear image quality at night. The IP66 weatherproof • Back Light Compensation (BLC) rating makes this dome camera suitable for • Digital Noise Reduction (DNR) outdoor applications. Costar's new line of HDTVI • Wide Dynamic Range (WDR) • Up-the-Coax (UTC) cameras are compatible with the ET Series DVRs and StarNET Video Management · Weatherproof IP66 Rated Software. StarNET is the remote access software • 12VDC or 24VAC that allows users to remotely view live and recorded video. StarNET incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.



CBT2S12IFW Specifications

Model	Lens	Resolution
CBT2S12IFW	2.8-12mm	2 Megapixel

Power		
Source	12VDC or 24VAC	
Consumption	4.5 watts (375mA@12VDC)	
Sensor and General Information		
Image Sensor	1/3" Panasonic CMOS	
Signal System	PAL/NTSC	
Resolution (H x V)	1920x1080	
Lens Focal Length	2.8-12mm	
Iris Control	Auto Iris	
Frame Rate	PAL:25fps ,NTSC:30fps	
IR LED	10pcs	
IR Wavelength	850nm	
IR Range	65 Feet (20m) Range	
	Color:1.0LUX, BW: 0.5 LUX	
Minimum Illumination	Color:DSS:0.017LUX,	
	BW DSS: 0.0008 LUX	
Shutter Speed	PAL:1/50-1/50000,	
	NTSC:1/60-1/60000	
S/N Ratio	More than 42dB(AGC off)	
Up-the-Coax	Pelco C, UTC (H)	
Video Features		
Max Distance	985 Feet (300m)	
	HD-TVI(1080P), HD-AHD(1080P)	
Video Output	CVBS(960H)1Vp-p Composite	
'	Output(75 Ω /BNC)	
Camera Functions		
Auto Gain Control	0-20 steps	
Brightness	0-20 steps	
Day & Night	Yes, IR Cut Filter	
Defog	Yes	
Motion Detection	Yes	
Digital Noise Reduction	Yes, 3D	
Wide Dynamic Range	120dB (WDR)	

General Information		
IP Rating	IP66	
Humidity	85% RH Max	
Temperature	14°F to 131°F	
	(-10°C to 55°C)	
Dimensions	3.16" x 10.41"	
	(80.3 x 264.5mm)	
Weight	1.653 lbs.	
Approvals	(750g) FCC, CE	
Арргочаю	100,02	
Dimensions		
10.41"		
3.16		
Accessories		
CDAJB10 Junction Box		

